



**Bazas**

Linear Design











### POWER AND LUMINOUS INTENSITIES PER MODULE - LUMINAIRE OUTPUT DATA

3000 K		350 mA			500 mA			700 mA		
Number of LED		P <sub>t</sub> (W)	Φ (lm)	(lm/W)	P <sub>t</sub> (W)	Φ (lm)	(lm/W)	P <sub>t</sub> (W)	Φ (lm)	(lm/W)
EVO 2	16	21.4	1988	93	28.2	2867	102	36	3636	101
	24	26.6	2982	112	37.4	4302	115	52.4	5455	104
	32	34.4	3976	116	48.8	5734	118	68.9	7271	106
	48	51	5964	117	72.6	8601	118	102.3	10907	107

4000 K		350 mA			500 mA			700 mA		
Number of LED		P <sub>t</sub> (W)	Φ (lm)	(lm/W)	P <sub>t</sub> (W)	Φ (lm)	(lm/W)	P <sub>t</sub> (W)	Φ (lm)	(lm/W)
EVO 2	16	21.4	2147	100	28.2	3097	110	36	3932	109
	24	26.6	3220	121	37.4	4646	124	52.4	5897	113
	32	34.4	4294	125	48.8	6193	127	68.9	7863	114
	48	51	6441	126	72.6	9290	128	102.3	11795	115

### ORDERING INFORMATION

Model	# LED	Current (mA)	CCT (K)	Distribution	Line Voltage	Mounting	Color
60006							
	16	350	3000	100°	220-240V	100°	3000K
	24	350	3000	112°	220-240V	112°	3000K
	32	350	3000	116°	220-240V	116°	3000K
	48	350	3000	117°	220-240V	117°	3000K
	16	500	3000	102°	220-240V	102°	3000K
	24	500	3000	115°	220-240V	115°	3000K
	32	500	3000	118°	220-240V	118°	3000K
	48	500	3000	118°	220-240V	118°	3000K
	16	700	3000	101°	220-240V	101°	3000K
	24	700	3000	104°	220-240V	104°	3000K
	32	700	3000	106°	220-240V	106°	3000K
	48	700	3000	107°	220-240V	107°	3000K
	16	350	4000	100°	220-240V	100°	4000K
	24	350	4000	121°	220-240V	121°	4000K
	32	350	4000	125°	220-240V	125°	4000K
	48	350	4000	126°	220-240V	126°	4000K
	16	500	4000	110°	220-240V	110°	4000K
	24	500	4000	124°	220-240V	124°	4000K
	32	500	4000	127°	220-240V	127°	4000K
	48	500	4000	128°	220-240V	128°	4000K
	16	700	4000	109°	220-240V	109°	4000K
	24	700	4000	113°	220-240V	113°	4000K
	32	700	4000	114°	220-240V	114°	4000K
	48	700	4000	115°	220-240V	115°	4000K



Bazas



A - Wall mounting



B - Square pole 800



C - Square pole 800



D - Square pole 800

Suggestions for ensembles

