



Syléa

Urban Ambiance





Syléa

Urban Ambiance

Lighting performance



AcuiSens V2 module

The AcuiSens V2 module is a compact LED module composed of 8 LEDs. Stélia uses the symmetrical distribution version. It owes its name on the one hand to the visual clarity it provides and, on the other hand, to the feeling of softness conveyed by its ambiance lighting.

- LED manufacturer: LUMILEDS
- LED life cycle: up to 100,000 hours
- Color temperatures: 3000k OR 4000k
- (other color temperatures on request)
- CRI above 70

Power and luminous intensity

3000K	350 mA			500 mA			700 mA		
	P _t (W)	Φ(lm)	(lm/W)	P _t (W)	Φ(lm)	(lm/W)	P _t (W)	Φ(lm)	(lm/W)
Number of LEDs									
8	18.5	2345	125	26.5	3320	124	38.5	4480	116

4000K	350 mA			500 mA			700 mA		
	P _t (W)	Φ(lm)	(lm/W)	P _t (W)	Φ(lm)	(lm/W)	P _t (W)	Φ(lm)	(lm/W)
Number of LEDs									
8	18.5	2460	132	26.5	3485	131	38.5	4706	122

P_t(W) = Total power consumption including driver consumption
 Φ Nominal flux (lm)
 Luminous efficiency (lm/W)

Ordering Information

Fixture	Module	Color Temp	Driving Current	Distribution	Line Voltage	Mounting	Color
SYL	AS2						
		3 – (3000 K)	35 – (350 mA)	T		TP – (Pole Top)	BLK – (Black)
		4 – (4000 K)	50 – (500 mA)	T5			BRZ – (Bronze)
			70 – (700 mA)				SLV – (Silver)
							WHT – (White)
							(RAL #)



Top mounted



Syléa
Suggestions for ensembles



A - Pelas350



B - Cyl400

St-Alban BRACKET



A - Wall mounting



B - Pelas400



C - Pelas400



D - Jima 500

Syléa

Urban Ambiance

